





# CPWplus L Floor Scales



## Speed, Performance, Value - The Right Balance

- Colour coded keys
- External calibration
- Four load cell construction
- Full range tare
- Kg/ lb/ oz/ lb & oz switchable
- Hold function
- Large backlit LCD display
- Mains adapter and wall mounting kit supplied as standard
- Portable with battery power
- RS-232 bi-directional interface
- Stainless steel weighing pan with remote indicator
- Simple 4 button operation
- Tare function
- Rechargeable battery or mains power
- Animal / dynamic weighing
- Weighing



## Technical Specifications

Model	CPWplus 35L	CPWplus 75L	CPWplus 150L	CPWplus 200L	CPWplus 300L
Maximum capacity	35kg	75kg	150kg	200kg	300kg
Readability	10g	20g	50g	50g	100g
Tare range	Full	Full	Full	Full	Full
Repeatability (S.D.)	10g	20g	50g	50g	100g
Linearity ( $\pm$ )	20g	40g	100g	100g	200g
Platform size	900x600mm				

## General Specifications

Units of measurement	Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Typical stabilisation time	2-3 Sec
Interface	RS-232 bi-directional Interface
Calibration	Automatic External with user selectable calibration mass
Display	LCD with minimum 25mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together
Operating temperature	0° 40°C
Housing	Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform
Overall dimensions (wxdxh)	900x600x80mm
Dimensions notes	Indicator: 220 x 95 x 43mm (w x d x h)
Net weight	17kg

## Key Accessories

- Adam Printer
- Thermal Paper Roll for Adam Printer
- RS-232 Cable
- AdamDU - Data Collection Program
- Rubber non-slip mat for CPWplus L



	Inscale Measurement Technology Ltd
	Unit 2, Hazel House, 78 London Road
	Bexhill, East Sussex
	TN39 3LE
	Tel: 01424 214215 Fax: 01424 215216 www.inscale-scales.co.uk



Adam Equipment - offices worldwide

[www.adamequipment.com](http://www.adamequipment.com)