





Speed, Performance, Value - The Right Balance

- Colour coded keys
- External calibration
- Four load cell construction
- Full range tare
- Kg/ lb/ oz/ lb & oz switchable
- Hold function
- Large backlit LCD display
- Mains adapter and wall mounting kit supplied as standard
- Portable with battery power
- RS-232 bi-directional interface
- Stainless steel weighing pan with remote indicator
- Simple 4 button operation
- Tare function
- Rechargeable battery or mains power
- Animal / dynamic weighing
- Weighing



Technical Specifications


Model	CPWplus 35M	CPWplus 75M	CPWplus 150M	CPWplus 200M
Maximum capacity	35kg	75kg	150kg	200kg
Readability	10g	20g	50g	50g
Tare range	Full	Full	Full	Full
Repeatability (S.D.)	10g	20g	50g	50g
Linearity (\pm)	20g	40g	100g	100g
Platform size	500x500mm			

General Specifications

Typical stabilisation time	2-3 Sec
Units of measurement	Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Interface	RS-232 bi-directional Interface
Operating temperature	0° - 40°C
Calibration	Automatic External with user selectable calibration mass
Display	LCD with minimum 25mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together
Housing	Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform
Overall dimensions (wxdxh)	500x500x40mm
Dimensions notes	Indicator: 270 x 80 x 30mm (w x d x h)
Net weight	8.5kg

Key Accessories

- Adam Printer
- Thermal paper roll for Adam printer
- AdamDU - Data Collection Programme
- RS-232 Cable



	Inscale Measurement Technology Ltd
	6 Endwell Road
	Bexhill, East Sussex
	TN40 1EA
	Tel: 01424 214215 Fax: 01424 215216 www.inscale-scales.co.uk



Adam Equipment - offices worldwide

www.inscale-scales.co.uk