

Stainless steel bench scale KERN FOB



Application examples:

- Weighing of ingredients and seasonings in the catering trade
- Portion division of dough, meat, fish, poultry, mixed salads in cafeterias, etc.
- Filling of canned goods
- Pre-packed goods controlling scale

- Overall dimensions WxDxH

A 235x175x60 mm

B 220x305x80 mm

- Net weight

A approx. 1,95 kg

B approx. 3,3 kg

- Permissible ambient temperature 0°C / 40°C

Verifiable stainless steel balance with special protection against humidity with EC-Type Approval [M]

Features

- **Stainless steel design** of the housing and weighing plate. Its smooth surfaces make it simple to clean
- **Increased protection against humidity** by means of waterproof silicone sealing of the load cell, electronics and soldering joints
- **High mobility:** thanks to battery operation (optional) and compact, flat construction, it is suitable for use in several locations (kitchen,

sales office, market stall, ...)

- **Net/Gross weight:** to control the consumed weighing range at the touch of a key

Technical data

- Large LCD display, digit height 25 mm
- Dimensions of weighing plate (stainless steel) WxD
 - A** 175x160 mm
 - B** 215x215 mm, see larger picture

Options

- **Protective working cover** over keyboard and housing, standard, can be reordered, for models with weighing plate sizes

A KERN FOB-A05

B KERN FOB-A06

- **Rechargeable battery pack internal.**

Charge condition indicator using three-colour LED, for weighing plate size

A operating time approx. 24 h, charging time approx. 8 h, KERN FOB-A07

B operating time approx. 30 h, charging time approx. 14 h, KERN FOB-A08

STANDARD



OPTION



STANDARD



OPTION



FACTORY



only FOB-M

Model	Weighing range [Max] kg	Read-out [d] g	Verific. value [e] g	Minimum load [Min] g	Weighing plate	Options		
						Verification		DKD Calibr. Certificate
						M	KERN	DKD KERN
FOB 1.5K0.5	1,5	0,5	-	-	A	-	-	963-127
FOB 7.5K0.5L	7,5	0,5	-	-	B	-	-	963-128
FOB 3K1	3	1	-	-	A	-	-	963-127
FOB 15K1L	15	1	-	-	B	-	-	963-128
FOB 6K2	6	2	-	-	A	-	-	963-128
FOB 30K2L	30	2	-	-	B	-	-	963-128
Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.								
FOB 1K1M	1	1	1	20	A	965-227	-	963-127
FOB 2K2M	2	2	2	40	A	965-227	-	963-127
FOB 5K5M	5	5	5	100	A	965-227	-	963-127
FOB 6K2LM *	6	2	2	40	B	950-128	-	963-128
FOB 15K5LM	15	5	5	100	B	950-128	-	963-128
FOB 30K10LM	30	10	10	200	B	950-128	-	963-128

■ * Only while stocks last

