


Precision balance KERN PKP



Robust laboratory and industrial scales with graphics display

Features

- The key to success in the laboratory, KERN 572, now also with clear graphics display
- **Weighing with tolerance range (check-weighing):** a visual signal helps with portion division, dispensing or grading
- **40 memories for each mode**
- **Functions:**
 - Capacity display
 - Dispensing assistance (subtractive, additive)
 - Piece counting with reference
 - Automatic reference optimisation
 - Tare deduction from the memory unit
 - Input of item or batch description, operator etc.
 - Freely programmable weighing unit, e.g. display directly in special units such as length of thread g/m, paper weight g/m², or similar

- Date/time
- Individual printout configuration
- **Robust metal housing**, ensures stability, protects the weighing technology elements and is robust enough to cope with everyday use

Technical data

- Backlit Graphic LCD display, screen diagonal 3,2" (approx. 81 mm)
- Dimensions of weighing plate (stainless steel)
 - A** ø 106 mm
 - B** ø 150 mm
 - C** 160x200 mm, see larger picture
- Overall dimensions WxDxH 180x310x90 mm
- Permissible ambient temperature 10°C / 40°C

Options

- **Protective working cover** standard, can be reordered, KERN 572-A02
- **Rechargeable battery pack external**, operating time approx. 25 h, charging time approx. 10 h, KERN KS-A01
- **Large glass draught shield** with 3 sliding doors for easy access to the items being weighed. Weighing space WxDxH 150x140x130 mm (only for models with weighing plate sizes **A**), KERN 572-A05
- **Matrix needle printer**, KERN 911-013
- **Thermal printer**, KERN YKB-01N
- **Statistics printer**, KERN YKS-01

For additional information on the printers see page 124

STANDARD



2 3

STANDARD


























OPTION



Model	Weighing range [Max] g	Read-out [d] g	Reproducibility g	Linearity g	Min. piece weight [PW min] g/piece	Net weight approx. kg	Weighing plate	Option	
								DKD Calibr. Certificate	DKD KERN
PKP 300-3	301	0,001	0,002	± 0,005	0,001	2,3	A	963-127	
PKP 420-3	421	0,001	0,002	± 0,005	0,001	2,3	A	963-127	
PKP 3000-2	3010	0,01	0,02	± 0,05	0,01	2,3	B	963-127	
PKP 4200-2	4210	0,01	0,02	± 0,05	0,01	2,3	B	963-127	
PKP 12K0.05	12100	0,05	0,05	± 0,15	0,05	2,7	C	963-128	
PKP 16K0.1	16100	0,1	0,1	± 0,3	0,1	2,7	C	963-128	
PKP 24K0.1	24100	0,1	0,1	± 0,3	0,1	2,7	C	963-128	

KERN Pictograms

 Internal adjusting (CAL): Quick setting of the balance's accuracy with internal adjusting weight (motordriven).	 Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required.	 Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.
 Rechargeable battery pack: rechargeable set.	 Power supply: integrated in balance. 230V/50Hz in Germany. On request GB, AUS or USA version.	 Mains adapter: 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.
 Battery operation: The battery type is specified for each device.	 Piece counting: Reference quantities selectable. Display can be switched from piece to weight	 Spray and dust protection IPxx The type of protection is shown by the pictogram. For details see the glossary.
 Data interface: The type of interface is shown by the pictogram. See the glossary for further details.	 GLP/ISO record keeping of weighing data with date, time and identification-no. Only with printers from KERN.	 Tare: put back displayed value to "0" during weighing process, e.g. to add or remove weighing material from a container.
 Dynamic weighing: Strong vibrations are filtered out to determine a stable weighing result.	 Stainless steel: the balance is protected against corrosion.	 Warranty: The warranty period is shown in the pictogram.
 Net-total weighing: weight of tare cup and weight of components memorized in two separate stores.	 Suspended weighing: load support with hook on the underside of the balance.	 Verification possible: The time required for verification is specified in the pictogram.
 Percentage determination: Determining the deviation in % from the target value (100%).	 Weighing with tolerance range: Upper and lower limiting can be programmed individually, e.g. dosing/sorting.	 DKD calibration possible: The time required for DKD calibration is specified in the pictogram.
 Package shipment via courier.	 Pallet shipment via freight forwarder.	[DMS] For details on weighing technologies, see the glossary.

Precision is our business

To ensure the high level of precision of your balance, KERN offers the appropriate test weight package for your balance. This consists of the test weight, box and DKD calibration certificate, as proof of its accuracy. The best way to ensure proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, and M3 with weights from 1 mg to 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.
(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DKD calibration of balances with a maximum load of up to 6000 kg
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages
D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponding test weight or the calibration service? Your KERN specialist dealer will be pleased to assist you.

Your KERN specialist dealer:

KERN – Professional measuring. Measuring technology and testing services from a single source



German Excellence Group
Member