

Stainless steel platform scale KERN SFB



Stainless steel platform scale with EC-Type Approval [M] and IP67

Features

- **1 Ideal for the robust industry**
- Scale entirely out of stainless steel
- Load cell steel, silicone-coated
- **Stand** to elevate display device, standard, for models with weighing plate sizes
 - A** height of stand approx. 200 mm
 - B** height of stand approx. 400 mm
- **Level indicator and foot screws** to level the balance precisely, fitted as standard, to give the most accurate weighing results
- **Load cell: IP67 protection:** high level of protection against dust and water. Ideal for

harsh environmental conditions. Designed for temporary use in wet areas

Technical data

- Large backlit LCD display, digit height 52 mm
- Dimensions of weighing plate (stainless steel) WxDxH
 - A** 300x240x100 mm
 - B** 400x300x128 mm, see larger picture
- Dimensions of display device WxDxH 266x165x96 mm
- Permissible ambient temperature -10°C / 40°C

- Rechargeable battery pack internal, standard, operating time approx. 80 h, charging time approx. 12 h

Options

- **Data interface RS 232 C**, interface cable included, approx. 1.5 m, must be ordered at purchase, KERN KFN-A01
- **Matrix needle printer**, KERN 911-013
- **2 Thermal printer**, KERN YKB-01N
- **3 Statistics printer**, KERN YKS-01

STANDARD



2 3

OPTION



STANDARD



OPTION



OPTION


























FACTORY



only SFB-M

Model	Weighing range [Max] kg	Read-out [d] g	Verific. value [e] g	Minimum load [Min] g	Cable length approx. m	Net weight approx. kg	Weighing plate	Options		
								Verification		DKD Calibr. Certificate
								M III KERN		DKD KERN
SFB 10K1HIP	10	1	-	-	1,7	9	A	-		963-128
SFB 20K2HIP	20	2	-	-	1,7	9	A	-		963-128
SFB 50K5HIP	50	5	-	-	1,7	9	A	-		963-128
SFB 50K5LHIP	50	5	-	-	1,7	14	B	-		963-128
SFB 100K10HIP	100	10	-	-	1,7	14	B	-		963-129
Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.										
SFB 15K5HIPM	15	5	5	100	1,7	9	A	965-228		963-128
SFB 30K10HIPM	30	10	10	200	1,7	9	A	965-228		963-128
SFB 60K20HIPM	60	20	20	400	1,7	9	A	965-229		963-129
SFB 60K20LHIPM	60	20	20	400	1,7	14	B	965-229		963-129
SFB 120K50HIPM	120	50	50	1000	1,7	14	B	965-229		963-129

KERN Pictograms

 Internal adjusting (CAL): Quick setting of the balance's accuracy with internal adjusting weight (motordriven).	 Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required.	 Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.
 Rechargeable battery pack: rechargeable set.	 Power supply: integrated in balance. 230V/50Hz in Germany. On request GB, AUS or USA version.	 Mains adapter: 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.
 Battery operation: The battery type is specified for each device.	 Piece counting: Reference quantities selectable. Display can be switched from piece to weight	 Spray and dust protection IPxx The type of protection is shown by the pictogram. For details see the glossary.
 Data interface: The type of interface is shown by the pictogram. See the glossary for further details.	 GLP/ISO record keeping of weighing data with date, time and identification-no. Only with printers from KERN.	 Tare: put back displayed value to "0" during weighing process, e.g. to add or remove weighing material from a container.
 Dynamic weighing: Strong vibrations are filtered out to determine a stable weighing result.	 Stainless steel: the balance is protected against corrosion.	 Warranty: The warranty period is shown in the pictogram.
 Net-total weighing: weight of tare cup and weight of components memorized in two separate stores.	 Suspended weighing: load support with hook on the underside of the balance.	 Verification possible: The time required for verification is specified in the pictogram.
 Percentage determination: Determining the deviation in % from the target value (100%).	 Weighing with tolerance range: Upper and lower limiting can be programmed individually, e.g. dosing/sorting.	 DKD calibration possible: The time required for DKD calibration is specified in the pictogram.
 Package shipment via courier.	 Pallet shipment via freight forwarder.	[DMS] For details on weighing technologies, see the glossary.

Precision is our business

To ensure the high level of precision of your balance, KERN offers the appropriate test weight package for your balance. This consists of the test weight, box and DKD calibration certificate, as proof of its accuracy. The best way to ensure proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, and M3 with weights from 1 mg to 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.
(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DKD calibration of balances with a maximum load of up to 6000 kg
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages
D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponding test weight or the calibration service? Your KERN specialist dealer will be pleased to assist you.

Your KERN specialist dealer:

KERN – Professional measuring. Measuring technology and testing services from a single source



German Excellence Group
Member